

Ice Merchandiser				Outside Dimensions			Solid Door	Approx. Ship.Wt.		Refrigeration	Amperage	
Models	No. of Doors	Capacity		Width	Depth	Height	Width X Height	Cold Wall	Auto Def.	Compressor	Cold Wall	Auto Def.
		Cu. Ft.	Bags (8 lbs.)									
300CW 300AD	1	30	100	36"	30"	79"	26" X 44"	350	365	1/4 hp	6.05	8.14
380CW 380AD	1	38	120	48"	35"	72"	27" X 27"	370	385	1/4 hp	6.05	8.14
420CW 420AD	1	42	125	48"	30"	79"	26" X 44"	385	400	1/4 hp	6.05	8.14
630CW 630AD	1	65	200	62"	35"	79"	26" X 44"	465	500	1/3 hp	9.5	12.08
600CW 600AD	2	60	200	72"	35"	72"	27" X 27"	470	500	1/3 hp	9.5	12.08
650CW 650AD	2	65	200	72"	30"	79"	26" X 44"	550	585	1/3 hp	9.5	12.08
670CW 670AD	2	65	200	62"	35"	79"	26" X 44"	560	570	1/3 hp	9.5	12.08
750CW 750AD	2	75	230	72"	35"	79"	26" X 44"	600	605	1/3 hp	9.5	12.08
850CW 850AD	2	85	255	84"	35"	79"	26" X 44"	620	645	1/2 hp	11.4	14.47
1000CW 1000AD	2	100	320	94"	35"	79"	26" X 44"	680	670	1/2 hp	11.4	14.47
400VTCW 400VTAD	2	40	120	72"	35"	49"	27" X 27"	460	480	1/4 hp	6.05	8.14
570VTCW 570VTAD	2	60	190	96"	35"	49"	27" X 27"	535	550	1/3 hp	9.5	12.08

Ice Merchandiser				Outside Dimensions			Glass Door	Approx. Wt.		Refrigeration	Amperage	
Models	No. of Doors	Capacity		Width	Depth	Height	Width X Height	Cold Wall	Auto Def.	Compressor	Cold Wall	Auto Def.
		Cu. Ft.	Bags (8 lbs.)									
300CWG 300ADG	1	30	100	36"	30"	79"	26" X 44"	350	390	1/4 hp	6.05	8.14
420CWG 420ADG	1	42	125	48"	30"	79"	26" X 44"	405	445	1/4 hp	6.05	8.14
630CWG 630ADG	1	65	200	62"	35"	79"	26" X 44"	505	525	1/3 hp	9.5	12.08
650CWG 650ADG	2	65	200	72"	30"	79"	26" X 44"	510	530	1/3 hp	9.5	12.08
670CWG 670ADG	2	65	200	62"	35"	79"	26" X 44"	580	600	1/3 hp	9.5	12.08
750CWG 750ADG	2	75	230	72"	35"	79"	26" X 44"	635	650	1/3 hp	9.5	12.08
850CWG 850ADG	2	85	255	84"	35"	79"	26" X 44"	650	690	1/2 hp	11.4	14.47
1000CWG 1000ADG	2	100	320	94"	35"	79"	26" X 44"	725	740	1/2 hp	11.4	14.47

Product improvement may require specifications to change without notice • Weights are crated weights  
 Add 3" for door and handle on upright models • Storage capacity may vary depending on loading methods and ice bags



**NOTE:**  
 All models are 115 volt, single phase, 60 hertz  
 All models are available in cold wall or auto defrost  
 Optional 220 volt, single phase, 50 hertz  
 Optional heavy duty refrigeration available on all models

